



client server and parallel worker thread spawn



Advanced Scholar Search

### Scholar Preferences

Scholar

Articles and patents

anytime

include citations



Create email alert

Results 21 - 30 of about 727. (0.25 sec)

High-level execution and communication support for **parallel** grid applications in JGrid

kwas.edu.pl PDF

S. Pota, Z. Juhász - Parallel and Distributed Processing .... 2006 - [ieeexplore.ieee.org](http://ieeexplore.ieee.org)

... represent the synchronous and asynchronous remote evaluation, with the `allocate()` method one can create message passing **parallel** applications, while ... than the URL classloader of the service downloads all the necessary class files from the **client** class **server** (2) making ...

Cited by 2 - Related articles - All 6 versions

Ninlet: a migratable **parallel** objects framework using Java

H. Takagi, S. Matsuoka, H. Nakada, S. ... - Concurrency: .... 1998 - interscience.wiley.com

... environment, but also could be used for implementing a virtual **parallel** computer on a ... can connect to the Dispatcher via a Web browser, displaying various **server** statuses as ... amongst multiple Dispatchers, avoiding the possible bottlenecks when the **client** requests concentrates ...

Cited by 54 - Referred articles - El Dirazi - All 4 versions

PDF An Assessment of the Apache Web Server 2.0 Performance on Linux

hanafos.com PDF

K Chong, MYSH Noh - ... of the 2002 International Symposium on .... 2002 - myfile.hanafos.com

... However, the results from the previous subsection do not support evidence of scalability for the MPM-worker. Table 4 shows the total number of children (that is, processes and/or threads) spawned for each of the server types when the client size is 150. ...

[Cited by 1](#) - [Related articles](#) - [View as HTML](#) - [All 3 versions](#)

[PDF] A Java **Parallel** Computing Framework for Heterogeneous Networks

osv.edu PDF

G. Mukarakate - 2002 - Cileseer

... [CM01] describe Computation eXchange (CX), a scalable and robust network for **parallel** computing. ... Basically, CX consists of the following entities: • Consumer - a **client** that needs computing resources; ... Task **Server** - a process that coordinates task distribution among a set of ...

[Cited by 1](#) · [Related articles](#) · [View as HTML](#) · [All 2 versions](#)

A framework of reusable structures for mobile agent development

arXiv.org [PDF]

T. Marian, B. Dumitriu, M. Dinsoreanu, I. ... - Arxiv preprint [cs/0605032](https://arxiv.org/abs/cs/0605032), 2006 - arxiv.org

... is the one that brings the **client** behavior to its end, thus terminating the current communication session with the **server** (the **thread** ... As a response to this, three such types of behaviors have been introduced: sequential, **parallel** and Finite State Machine (FSM), and more can ...

[Cited by 3](#) - [Related articles](#) - [View as HTML](#) - [All 7 versions](#)

V Beltran, D Carrera, J Torres, E Ayquade - 2004 - comouter.org

Cited by 15 - Rejected articles - All 15 versions

www.ck12.org

P. Li, S. Zdancewicz - ACM SIGPLAN Notices, 2007 - portal.acm.org

... with monadic **threads** in the do-syntax, the programmer can write code for each **client** session in ... the accepted connection is returned, otherwise it waits for an EPOLL READ event on the **server** socket, indicating ... The **worker main** event loops are simply **thread** schedulers; they ...

Cited by 30 - Related articles - BL Direct - All 10 versions

H. Cejtin, S. Jacobson, R. Kelsey - US Patent 5,745,703, 1998 - Google Patents

... map (lambda (aspace) (remote-apply aspace make-proxy ())) **worker-aspace**s)) (values ... for **threads**, incrementally- linked distributed computations, and parameterized **client-server** applications, facilitate ... These issues concern the interaction of **parallel** and distributed tasks with ...

Cited by 23 - Related articles

## 031.001 1995

P.L.S. Zdanczewicz - 2006 - Citesser

... **server** = do { sys\_call\_1; fork **client**; **server**; } **client** = do { sys\_call\_2 ... the accepted connection is returned, otherwise it waits for an EPOLL READ event on the **server** socket, in ... round-robin scheduler: it uses a task queue called ready queue and an event loop called **worker main**. ...

[Cited by 2](#) - [Related articles](#) - [View as HTML](#) - [All 7 versions](#)

## temple.edu/PDF

B. RoussevQ. J. Wuæ - cis.temple.edu

... where the **server** spawns a new **thread** to handle the **client** connection. ... Theoretically, this **server** design should give good performance when the load factor ' approaches 1. ... 3. GC Fox and W. Furmansk, "Java for **parallel** computing and as a general language for scientific and ...

[Related articles - View as HTML - All 3 versions](#)

☒ Create email alert

Result Page: [Previous](#) [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [11](#) [12](#) [Next](#)

client server and parallel worker thr

Search

[Go to Google Home](#) - [About Google](#) - [About Google Scholar](#)

©2010 Google